

MATERIAL SAFETY DATA SHEET

Page 1

MANUFACTURERS' NAME: **ADVANCED COATINGS & CHEMICALS**
 Subsidiary of Olin Hunt Specialty Products, Inc.
 4343 Temple City Blvd.
 Temple City, CA 91780

DATE OF PREPARATION: 9-16-86

EMERGENCY PHONE NO: **(818) 579-6270**

SECTION I—PRODUCT IDENTIFICATION

PRODUCT FORMULA: 3-1X-7
 PRODUCT NAME: URAFILM TFE GRAY
 PRODUCT CHEMICAL FAMILY: POLYTETRAFLUORIDE ETHYLENE

SECTION II—HAZARDOUS INGREDIENTS

INGREDIENTS	CAS NUMBER	EXPOSURE LIMITS IN AIR		IARC, NTP OSHA HAZARD EVALUATION
		OSHA PEL	ACGIH TLV	
POLYTETRAFLUORIDE ETHYLENE	9002-84-0	15mg/m ³	10mg/m ³	NON-CARCINOGENIC
EPOXY	25068-38-6	5 ppm	2 ppm	EPICHLORMYDRIN-CARCINOGEN, IARC V.11
				Page 131
AZELAIC ACID	123-99-9	Not Est.	Not Est.	NON-CARCINOGENIC
TITANIUM DIOXIDE	1314-13-2	15mg/m ³	5 mg/m ³	NON-CARCINOGENIC
BARYTES	7727-47-7	15 mg/m ³	10 mg/m ³	NON-CARCINOGENIC
LUMINA	1344-28-7	5 mg/m ³	10 mg/m ³	NON-CARCINOGENIC
ETHYL 3-ETHOXY PROPIONATE	763-69-0	Not Est.	Not Est.	NON-CARCINOGENIC
METHYL NORMAL AMYL KETONE	110-43-0	100 ppm	100 ppm	IRRITANT; MILDLY TOXIC
METHYL ETHYL KETONE	78-93-3	200 ppm	200 ppm	NON-CARCINOGENIC
				NARCOTIC
CARBON BLACK	1333-86-4	3.5 mg/m ³	3.5 mg/m ³	NON-CARCINOGENIC
YELLOW IRON OXIDE	12259-21-1	10mg/m ³	5 mg/m ³	NON-CARCINOGENIC

SECTION III—PHYSICAL DATA

BOILING POINT: 175°F	SPECIFIC GRAVITY: 1.21
VAPOR DENSITY (AIR = 1): HEAVIER	% VOLATILE BY VOLUME: 56%
SOLUBILITY IN WATER: NEGLIGIBLE	EVAPORATION RATE: SLOWER
VAPOR PRESSURE: @20°C 70 mm.Hg.	(BUTYL ACETATE = 1)

SECTION IV—FIRE AND EXPLOSIVE HAZARD DATA

FLASH POINT: 20 °F. TCC LEL: 1.05 % by Volume UEL: 10.0 % By Volume

EXTINGUISHING MEDIA: Foam, Dry Chemical, CO₂ and/or Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS:

During a fire, irritating and toxic gases and smoke are present from decomposition. Isolate from heat, sparks and open flames. Closed containers may burst when exposed to extreme heat. Vapors form an explosive mixture in air between the upper and lower explosive limits.

SPECIAL FIREFIGHTING PROCEDURES: Full emergency equipment with self-contained breathing apparatus should be worn by firefighters.

BOE-C6-0227049